

## **Transmitter Accessories and Signal Clamps**

Direct Connection Leads and Accessories													
Picture	Order Code	Description	Plug Type	1-Watt 5-Watt 10-Watt	25-Watt	VM-550FF VM-560FF	VM-810 VM-850 vScan						
Direct Connection Lead, Standard Clips													
	2.205.01.00018	Direct Connection Lead with Standard Clips are for day to day use where the		$\bigcirc$	-	<b>⊘</b>	$\bigcirc$						
	2.222.02.00007	size of the targeted lines varies, and connections are to common services.		-	<b>⊘</b>	-	-						
Direct Connection Lead with large clips													
	2.213.02.00013	Direct Connection Lead with large clips is suited for the gas and water industries where connections will		<b>⊘</b>	-	<b>⊘</b>	<b>⊘</b>						
	2.219.02.00090	be made to bell housings or fire hydrants.		-	<b>⊘</b>	-	-						
Direct Connection	n Lead with Telco	Clip											
	2.213.02.00007	Direct Connection Lead with Telco clips is suitable for telephone cable where		<b>⊘</b>	-	<b>Ø</b>	<b>⊘</b>						
	2.219.02.00091	the user cannot access the sheath of the cable.		-	<b>✓</b>	-	-						
Ground Extension	n Lead												
	2.200.04.00082	Ground Extensions - Use the extension	30 feet	<b>⊘</b>	<b>⊘</b>	<b>⊘</b>	<b>⊘</b>						
	2.200.04.00081	leads to extend the ground connection to reach a suitable grounding position.	98 feet	<b>⊘</b>	<b>⊘</b>	<b>Ø</b>	<b>⊘</b>						
Clamp and Leads	Adapter												
	2.219.02.00094	Adapter, 3 pin silver plug to Twist/Lock plug.	-	<b>⊘</b>	-	<b>⊘</b>	<b>⊘</b>						
Live Cable Conne	ctor												
	1.204.10.00001	Live Cable Connector is usable on live cables up to 480 V ac 60/50Hz. The		<b>⊘</b>	-	<b>⊘</b>	<b>⊘</b>						
A TA	1.204.10.00002	Live Cable Connector operates on frequencies of 8kHz, 33kHz and SIS.		-	<b>✓</b>	-	-						
Live Plug Connec	tor												
	1.204.07.00002	Live Plug Connector is used to safely inject a locate frequency onto a live		<b>⊘</b>	-	<b>⊘</b>	V						
	1.204.07.00005	street distribution cable using a standard household mains socket from a building.		-	<b>⊘</b>	-	-						

Transmitter Clamps											
Picture	Order Code	Description	Plug Type	5-Watt 10-Watt SiS	25-Watt	VM-550FF VM-560FF vScan	VM-810	VM-850			
~	1.200.03.00011	2" / 50mm		<b>⊘</b>	-	<b>⊘</b>	<b>⊘</b>	<b>⊘</b>			
	1.200.15.00001	Signal Clamp	1110	-	<b>✓</b>	-	-	-			
	1.200.03.00012	4" / 100mm		<b>✓</b> *	-	<b>⊘</b>	<b>⊘</b>	<b>⊘</b>			
	1.222.03.00001	Signal Clamp		*	<b>✓</b>	-	-	-			
	1.200.03.00004	5" / 125mm		<b>*</b>	-	<b>⊘</b>	V	V			
	1.222.04.00001	Signal Clamp		<b>*</b>	<b>⊘</b>	-	-	-			
	1.219.09.00001	5" / 125mm SiS Signal Clamp		<b>⊘</b>	<b>⊘</b>	-	-	-			
	1.219.08.00002	9" / 230mm		<b>*</b>	-	<b>⊘</b>	<b>⊘</b>	<b>⊘</b>			
	1.219.08.00001	Signal Clamp		<b>*</b>	<b>⊘</b>	-	-	-			
	1.200.03.00006	18" / 450mm Flexible Signal Clamp		<b>⊘</b>	-	<b>⊘</b>	<b>⊘</b>	-			
Clamp and Leads Adapter											
	2.219.02.00094	Adapter, 3 pin silver plug to Twist/Lock plug.		<b>⊘</b>	-	<b>⊘</b>	<b>⊘</b>	<b>⊘</b>			
Clamp extension rod											
	1.204.08.00001	The extension rod is compatible with all clamps except the 18" flexible.									

**Local Vivax-Metrotech Distributor:** 

Twist/Lock plug

3 Pin Silver Plug

## Vivax-Metrotech Ltd.

Unit 1, B/C Polden Business Centre, Bristol Road, Bridgwater, Somerset, TA6 4AW, UK

Tel: +44(0)1793 822679 Email: SalesUK@vxmt.com www.vivax-metrotech.co.uk

Tag us on social media @vivax\_metrotech











\*SiS 8.44kHz and 9.82kHz